CABLECOMM ENGINEERING PTE. LTD.
10 Jalan Besar #02-10 Sim Lim Tower Singapore 208787.
Tel: 6291 6566 Fax: 6291 1887
Company Reg. NO.: 201218346Z
GST Reg NO.: 201218346Z

Standalone Access Controller Reader

Stainless Steel Body Card + Password Door Bell Support

- Metal case, Anti-Vandal
- Easy to install and program
- Full programming from the keypad
- 2000 users, supports Card, PIN, Card+PIN
- Backlight keypad
- Adjustable alarm output time and relay output time
- Low power consumption (30mA)
- Fast operating speed, <20ms with 2000 users
- Lock output current short circuit protection
- Built-in light dependent resistor (LDR) for Anti-Tamper
- Built-in buzzer
- Red, Yellow and Green LEDs display the working status

Model Number	AC-5008B/S500
Dimensions	80(L) x 25(W) x 120(H) mm
Capacity	2000 users
Reading Range	3 ~ 6 cm
DC Supply Voltage	DC12V±10%
Active Current	<60mA
Static Current	<30mA
Ambient Temperature	-25°C ~ 60°C
Ambient Humidity	10% - 90%
Electricity Lock Output	Max 3A
Alarm Output	Max 20A
Short Circuit Protection Time	<=100uS
Adjustable Door Relay Time	0 - 99 seconds
Adjustable Alarm Time	0 - 3 min
Wiegand Interface	Wiegand 26 bits I/O
Wiring Connections	Electric Lock, Exit Button, External Door Bell ...