

Video/Audio Input		
Audio Input:		1-ch
Video Compression:		H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Analog and HD-TVI video input:		16-ch,BNC interface (1.0Vp-p, 75 Ω)connection
Supported camera types:		Support HDTVI input: 4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25
		Note: The 3 MP signal input is only available for channel 1/2 of DS-7208HQHI-K2, and for channel 1/2/3/4 of DS-7216HQHI-K2.
		Support AHD input: 4 MP, 1080p25, 1080p30, 720p25, 720p30
		Support CVI input: 1080p25, 1080p30, 720p25, 720p30
		Support CVBS input
Video Input Interface:		BNC (1.0 Vp-p, 75Ω)
Audio Compression:		G.711u
Audio Input Interface:		RCA (2.0 Vp-p, 1 kΩ)
Two-way Audio:		1-ch, RCA (2.0 Vp-p, 1 kΩ), (using the 1st channel of audio input)
Video/Audio Output		
CVBS Output:		1-ch,BNC(1.0Vp-p,75Ω),resolution:PAL:704x576,NTSC:704x480
HDMI/VGA Output:		VGA: 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
		HDMI: 1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Recording resolution:		When 1080p Lite mode not enabled:
		4 MP lite/3 MP/1080p/1080p lite/720p/WD1/4CIF/VGA/CIF
		When 1080p Lite mode enabled:
		4 MP lite/3 MP/1080p lite/720p/720p lite/WD1/4CIF/VGA/CIF
		Main stream:
		When 1080p Lite mode not enabled:

Frame Rate:		For 4 MP stream access: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N)
		For 3 MP stream access: 3 MP/1080p/720p/VGA/WD1/4CIF/CIF@15fps
		For 1080p stream access: 1080p@15fps; 720p/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N)
		For 720p stream access: 720p/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N)
		When 1080p Lite mode enabled:
		4 MP lite/3 MP@15fps; 1080p lite/720p lite/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N)
		Sub-stream:
		WD1/4CIF@12fps; CIF@25fps (P)/30fps (N)
Video Bit Rate:		32 Kbps-6 Mbps
Stream Type:		Video/Video&Audio
Two-way Audio:		1-ch, RCA (2.0 Vp-p, 1 kΩ) (using the audio input)
Audio Output:		1-ch RCA(Linear, 1kΩ)
Audio Bit Rate:		64kbps
Dual Stream:		Support
Synchronous Playback:		16-ch
Network management		
Remote connections:		128
Network protocols:		TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP?, HTTPS, ONVIF
Hard Disk Driver		
Interface Type:		2 SATA Interfaces
Capacity:		Up to 10 TB capacity for each disk
External Interface		
Network Interface:		1; 10M / 100M / 1000M self-adaptive Ethernet interface
USB Interface:		1 USB 2.0 Interface & 1 USB 3.0 Interface
Serial Interface:		1; standard RS-485 serial interface, half-duplex
General		

Power Supply:		12 VDC
Consumption:		≤ 25W(without hard disks)
Working Temperature:		-10 oC to +55 oC (14 oF to 131 oF)
Working Humidity:		10% to 90%
Dimensions:		380 × 320 × 48 mm (15.0 × 12.6 × 1.9 inch)
Weight:		≤ 2 kg (4.4 lb)